


Versailles

Rovere Oak



Quadratta “Versailles”

“Versailles” Panel



CARATTERISTICHE

- Quadratta mod. 248 stile “Versailles”
- Primo strato di legno nobile di spessore 3mm
- Incastro maschio e femmina sui 4 lati del pannello
- Oliato naturale
- Posa incollata
- Bisellatura perimetrale

L'umidità ambientale d'esercizio deve essere compresa tra il 45% ed il 60% ad una temperatura di circa 20°C.

N.B.

Il legno è un materiale naturale, ogni tavola è un esemplare unico, per questo motivo più tavole possono differire tra loro nel colore.

—
Si sconsiglia l'uso di nastro adesivo sulle finiture in quanto può danneggiare la superficie.

CHARACTERISTICS

- Pattern mod. 248 style “Versailles”
- Top layer prestigious wood, thickness 3mm
- Tongue and groove on the 4 sides of the pannel
- Natural oiled
- Glued installation
- Bevelled perimeter

The operating environmental humidity must be between 45% and 60% at a temperature of approximately 20°C.

Please note:

Wood is a natural product and each plank is a unique specimen, hence planks may differ one from the other in colour.

—
The use of adhesive tape on the finishes is not recommended as it can damage the surface.



Parquet multistrato 1strip
Engineered wood flooring 1strip



P01 Prelevigato
Unfinished

SPESS./THICK 14mm
LARGH./WIDTH 600mm
LUNGH./LENGTH 600mm
VENERE



U01 Vernice OIL UV
OIL UV Varnish

SPESS./THICK 14mm
LARGH./WIDTH 600mm
LUNGH./LENGTH 600mm
VENERE



P01 Prelevigato
Unfinished

SPESS./THICK 14mm
LARGH./WIDTH 1000mm
LUNGH./LENGTH 1000mm
VENERE
