


# Spina Herringbone

## Essenze Wood species



### Spina tradizionale

*Classic herringbone*



#### CARATTERISTICHE

- Supporto in multistrato
- Incastro maschio e femmina su 4 lati
- Primo strato di legno nobile 3-4mm
- Posa incollata

L'umidità ambientale d'esercizio deve essere compresa tra il 45% ed il 60% ad una temperatura di circa 20°C.

**N.B.**

Il legno è un materiale naturale, ogni tavola è un esemplare unico, per questo motivo più tavole possono differire tra loro nel colore.

—  
Si sconsiglia l'uso di nastro adesivo sulle finiture in quanto può danneggiare la superficie.

#### CHARACTERISTICS

- Plywood support
- Tongue and groove on 4 sides
- Top layer prestigious wood 3-4mm
- Glued installation

*The operating environmental humidity must be between 45% and 60% at a temperature of approximately 20°C.*

**Please note:**


*Wood is a natural product and each plank is a unique specimen, hence planks may differ one from the other in colour.*

—  
*The use of adhesive tape on the finishes is not recommended as it can damage the surface.*



Parquet multistrato 1strip  
*Engineered wood flooring 1strip*

Noce Walnut



U01 Vernice OIL UV

Masseria

**SPESS./THICK** 14mm  
**LARGH./WIDTH** 90mm  
**LUNGH./LENGTH** 600mm

**VENERE**

Noce Walnut



U01 Vernice OIL UV

Villa

**SPESS./THICK** 12mm  
**LARGH./WIDTH** 150mm  
**LUNGH./LENGTH** 500/1020mm

**CLASSIC**

Teak Teak



U01 Vernice OIL UV

Masseria

**SPESS./THICK** 14mm  
**LARGH./WIDTH** 90mm  
**LUNGH./LENGTH** 600mm

**VENERE**

Teak Teak



U01 Vernice OIL UV

Villa

**SPESS./THICK** 10mm  
**LARGH./WIDTH** 120mm  
**LUNGH./LENGTH** 500/700mm

**CLASSIC**