


Spina Chevron 45°

Essenze Wood species



Spina Ungherese 45°

Chevron 45°



CARATTERISTICHE

- Supporto in multistrato
- Incastro maschio e femmina su 4 lati
- Primo strato di legno nobile 3-4mm
- Angoli Bisellati
- Posa incollata

L'umidità ambientale d'esercizio deve essere compresa tra il 45% ed il 60% ad una temperatura di circa 20°C.

N.B.

Il legno è un materiale naturale, ogni tavola è un esemplare unico, per questo motivo più tavole possono differire tra loro nel colore.

—
Si sconsiglia l'uso di nastro adesivo sulle finiture in quanto può danneggiare la superficie.

CHARACTERISTICS

- Plywood support
- Tongue and groove on 4 sides
- Top layer prestigious wood 3-4mm
- Bevelled Edges
- Glued installation

The operating environmental humidity must be between 45% and 60% at a temperature of approximately 20°C.

Please note:


Wood is a natural product and each plank is a unique specimen, hence planks may differ one from the other in colour.

—
The use of adhesive tape on the finishes is not recommended as it can damage the surface.



Parquet multistrato 1strip
Engineered wood flooring 1strip

Noce Walnut




U01 Vernice OIL UV
OIL UV Varnish

Masseria

SPESS./THICK 14mm
LARGH./WIDTH 90mm
LUNGH./LENGTH 510mm
VENERE

Noce Walnut




U01 Vernice OIL UV
OIL UV Varnish

Villa

SPESS./THICK 12mm
LARGH./WIDTH 150mm
LUNGH./LENGTH 600mm
CLASSIC

Teak Teak




U01 Vernice OIL UV
OIL UV Varnish

Masseria

SPESS./THICK 14mm
LARGH./WIDTH 90mm
LUNGH./LENGTH 600m
VENERE

Teak Teak



U01 Vernice OIL UV
OIL UV Varnish

Villa

SPESS./THICK 10mm
LARGH./WIDTH 120mm
LUNGH./LENGTH 600mm
CLASSIC
